

S645PG3

(Additional 3 GigaLAN + Express card slot + Mini PCIe slot)

SPECIFICATION

- **Core Logic**
Intel GM45/ICH9M
- **Processor**
Support Socket P, FSB 667/800/1066MHZ
Intel Mobil CPU Celeron M 575, 585 ;
Core2Duo T7500, T9400, T9600, P8400 & P8600 CPU
- **Memory**
Support SODIMM, DDR II 667/800MHz *2; Memory size up to 4GB
- **Graphics**
Integrated Intel Graphics Media Accelerator 4500MHD
- **Audio**
High definition 6 channels audio CODEC
- **LAN**
Built-in Four Intel 82573L 10/100/1000Mbps ethernet controllers
- **Fire Wire**
Built-in OHCI 1394a 1.1 compliance; Support up to 400Mb transfer rate
- **Storage Devices**
Support 2.5" SATA hard disk drive
Support SATA Slim DVD-ROM Combo, DVD-RW drive
- **Hardware Monitor**
CPU temperature, cooling fan speed, system voltage
- **Power Management**
ACPI 3.0 compliance OS direct power management; Wake-on event
- **Switches and Connection**

Front Panel:

1 x IEEE 1394 Fire wire port; 1 x USB 2.0 / 1.1 Port
1 x MIC Port;
Power-on & Reset buttons; Power and HDD LED

Back Panel:

1 x VGA port
1 x RS232(COM) port
1 x Line-Out Phone Jack
4 x RJ45 10/100/1000Mb Fast Ethernet
1 x PCI-E Express card slot
1 x Mini PCI-e/USB 2.0 mini card slot (*Not support SATA or PATA SSD mini card*)
2 x PS/2 Ports for Keyboard & Mouse
2 x USB 2.0 / 1.1 Ports;
1 x DC 12V Power-in Jack

- **Dimension**
146 x 250 x 42 mm
- **AC/DC Adaptor**
Universal 100~240V AC in/12V DC out power adaptor
- **Accessories**
Power Adaptor, Driver CD, User's Guide, CPU Cooler, Screws Pack

