

S345S

SPECIFICATION

- **Core Logic**
Intel GM45/ICH9M
- **Processor**
Support Socket P, FSB 667/800/1066MHZ
Support Intel Mobil CPU Celeron M 575, 585, T3100 ;
Core2Duo P8400 & P8600 CPU
- **Memory**
Support SODIMM, DDR III 800/1066MHz *2; Memory size up to 4GB
- **Graphics**
Integrated Intel Graphics Media Accelerator 4500MHD
- **Audio**
High definition 6 channels audio CODEC
- **LAN**
Built-in Intel 10/100/1000Mbps Ethernet controller
- **Storage Devices**
Support 2.5" SATA hard disk drive
- **Hardware Monitor**
CPU temperature, cooling fan speed, system voltage
- **Power Management**
ACPI 3.0 compliance OS direct power management; Wake-on event
- **Switches and Connecting Ports**
 - Front Panel:**
 - 2 x RS232(COM) ports
 - 2 x USB 2.0 ports
 - 1 x MIC phone jack
 - 1 x Ear phone kack
 - Power-on button
 - Power/HDD LED
 - Back Panel:**
 - 1 x DVI-I port
 - 1 x RJ45 10/100/1000Mb LAN port
 - 2 x PS/2 ports for Keyboard & Mouse
 - 1 x USB 2.0 / 1.1 port
 - 1 x DC 12V Power-in connector
- **Dimension & Volume**
102 x 155 x 37 mm; 0.58 Liter
- **AC Adaptor**
Universal 100~240V AC in/12V DC out 60W Power Adaptor
- **Accessories**
Power Adaptor, DVI to VGA converter; Driver CD, User's Guide, CPU Cooler, Screws Pack

